

TA-AP818P HDMI SWITCH 8*1-4K@60HZ



Item		Description
Model No.		TA-AP818P
Features	Function	8 HDMI input signals to 1 HDMI output switch
	Transmission signal	HDMI
	Channel	HDMI input ×8, HDMI output ×1
	Distance	10m
	RS232 Control	support
	Remote control	support
	Button control	support
Power supply	Power supply	Power Adapter
	Voltage/current	DC5V2A
	Consumption	<5W
HDMI Capability And Ports	HDMI Version	HDMI2.0
	HDCP Compatibility	HDCP2.2
	Resolution	4K×2K@60Hz
	Audio Format	Standard audio, DSD (Direct stream digital) ,and HBR
	Input TMDs Signal	0.5~1.5Vp-p(TMDs)
	Input DDC Signal	5Vp-p(TTL)
	Input Cable Length	≤5m(AWG26 HDMI2.0 Cable standards) ≤10m(AWG23 HDMI2.0 Cable standards)
	Output Cable Length	≤5m(AWG26 HDMI2.0 Cable standards) ≤10m(AWG23 HDMI2.0 Cable standards)
Protection	ESD protection	1a Touch Discharge 3 Class 1b Air Discharge 3 Class Standard : IEC61000-4-2
Operational Environment	Working Temperature	0~60°C
	Storage Temperature	-20~70°C
	Humidity	0~95%
Mechanical	Dimension	276 x 110 x 25mm
	Material	Ferroalloy + Clear Panel
	Craft	Ferroalloy
	Color	Black

	Weight	400g
Compliances		CE, ROHS, FC, UKCA